

Vertical display freezers [ventilated]



-15/-25°C



**CRFV 500**  
667 x 680 x 2018  
420lt



**CRFV 500 FRAMELESS**  
667 x 680 x 2018  
420lt

**Advantages**

- High aesthetics
- Ideal for promoting frozen products
- Selected by leading companies in the ice cream sector
- Maximum use of limited spaces
- Large display area optimum product promotion
- Robust for heavy duty-use
- Plug ready

**Basic Equipment**

- Hi efficiency compressor
- Ventilated refrigeration
- Digital controller
- Automatic fan switch off with door opening.
- High temperature alarm
- Automatic defrost
- 5 adjustable reinforced shelves
- Illuminated LED canopy
- Internal LED light
- Operation switch
- Antidazzle triple glass door
- Two regulators
- Four castor wheels
- Self closing door
- Easily removable grille and canopy
- Air cooled condenser
- Internal body from non toxic pre-painted steel sheet

**Optional Equipment**

- Shelves
- Maintenance free condenser
- EBD electronic fan motor (compressor)
- Branding

**Technical Specifications**

TECHNICAL SPECIFICATIONS	UNITS	CRFV 500	CRFV 500 FRAMELESS
External dimensions (lxwxh)	mm	667 x 680 x 2018	667 x 680 x 2018
Internal dimensions (lxwxh)	mm	547 x 490 x 1553	547 x 490 x 1553
Packing dimensions (lxwxh)	mm	680 x 707 x 2100	680 x 707 x 2100
Internal gross volume	lt	420	420
Temperature range	°C	-15 / -25	-15 / -25
Gross / net weight	kg	137 / 129	137 / 129
Energy consumption*	kW/24h	10.09	10.09
Pieces per truck 13.6m	-	57	57
Pieces per 20/40'ft container	-	24 / 51	24 / 51
Refrigeration	-	AIR COOLED	AIR COOLED
Refrigerant	-	R290	R290

\*The energy consumption concerns specific metrics

