


CRF 400 / FRAMELESS

Vertical display freezer [static]



-18/-25°C 



CRF 400
667 x 620 x 2018
417lt



CRF 400 FRAMELESS
667 x 620 x 2018
417lt



Advantages

- High aesthetics
- Ideal for promoting frozen products
- Selected by leading companies in the ice cream sector
- Maximum use of limited spaces
- Large display area for optimum product promotion
- Robust for heavy-duty use
- Plug ready



Basic Equipment

- Hi efficiency compressor
- Digital controller
- Internal LED light
- Antidazzle triple safety glass door
- Easily removable grill
- Evaporation shelves (6pcs) + floor shelf (distance shelves 19 cm)
- Self closing door
- Four castors
- Two regulators
- Air cooled condenser
- Drainage
- Internal body from non toxic pre-painted steel sheet



Optional Equipment

- Maintenance free condenser
- EBD electronic fan motor (compressor)
- Branding
- Remote Controller:
 1. Online temperature (The temperature of the device is available on the mobile device of the user through the app or the e-mail)
 2. Temperature history (The user has access to the temperature history of the device through the app)
 3. Alarm (The user receives an alarm on the mobile device in the unlikely event of power failure or malfunction of the device)
 4. Export reports to PDF or CSV (Excel).



Technical Specifications

TECHNICAL SPECIFICATIONS	UNITS	CRF 400	CRF 400 FRAMELESS
External dimensions (lxwxh)	mm	667 x 620 x 2018	667 x 620 x 2018
Internal dimensions (lxwxh)	mm	547 x 490 x 1553	547 x 490 x 1553
Packing dimensions (lxwxh)	mm	710 x 645 x 2110	710 x 645 x 2110
Internal gross volume	lt	417	417
Temperature range	°C	-18 / -25	-18 / -25
Energy consumption	kW/24h	8,270	8,270
Gross / net weight	kg	122/ 116	124 / 118
Climate class	-	7L1/5L1	7L1/5L1
Pieces per truck 13.6m	-	60	60
Pieces per 20/40'ft container	-	24 / 54	24 / 54
Refrigeration	-	STATIC WITH SHELVES	STATIC WITH SHELVES
Refrigerant	-	R290	R290

*The energy consumption concerns specific metrics

